



15A34D

2-way Configuration With Active Filter
CLASS D Bi-AMP, USB, MP3, Stereo

Bluetooth

EQ: 80Hz, 12kHz

With DSP processor and 4 modes can be selected

Mic Input: XLR or 1/4" Jack

Line Input: XLR, RCA, 3.5mm Jack

Line Output: XLR

RMS Power: 800W

Power Voltage: AC100V - AC240V



15A34H

2-way Configuration With Active Filter
CLASS H Bi-AMP, USB, MP3, FM

Radio, Stereo Bluetooth

EQ: 80Hz, 12kHz

With DSP processor and 4 modes can be selected

Mic Input: XLR or 1/4" Jack

Line Input: XLR, RCA, 3.5mm Jack

Line Output: XLR

RMS Power: 800W

Power Voltage: AC115V / AC230V



15A36D

2-way Configuration With Active Filter
CLASS D Bi-AMP

Mic Input: XLR or 1/4" Jack (2 way)

Line Input: XLR or 1/4" Jack (2 way)

Line Output: XLR

RMS Power: 800W

Power Voltage: AC100V - AC240V



15A36H

2-way Configuration With Active Filter
CLASS H Bi-AMP

Frequency Range: 45Hz-20KHz

Mic Input: XLR or 1/4" Jack (2 way)

Line Input: XLR or 1/4" Jack (2 way)

Line Output: XLR

RMS Power: 800W

Power Voltage: AC115V / AC230V



15A37

2-way Configuration With Active Filter
CLASS D Bi-AMP, Bluetooth

With DSP processor and 4 modes can be selected

Mic Input: XLR or 1/4" Jack (2-way)

Line Input: XLR or 1/4" Jack

Line Output: XLR

RMS Power: 800W

Power Voltage: AC100V - AC240V



15A38D

2-way Configuration With Active Filter
CLASS D Bi-AMP, Bluetooth

Frequency Range: 45Hz-20KHz

With DSP processor and 5 modes can be selected

Mic Input: XLR or 1/4" Jack (2-way)

Line Input: XLR or 1/4" Jack, RCA

Line Output: XLR

RMS Power: 800W

Power Voltage: AC100V - AC240V



15A38H

2-way Configuration With Active Filter
CLASS H Bi-AMP, Bluetooth

With DSP processor and 5 modes can be selected

Mic Input: XLR or 1/4" Jack (2-way)

Line Input: XLR or 1/4" Jack, RCA

Line Output: XLR

RMS Power: 800W

Power Voltage: AC115V / AC230V